

MP550N Speaker

OPUS INTEGRATED SYSTEM™ COMPONENT SPECIFICATIONS

Applications:

- Stage Monitors
- DJ Monitors
- Zone Fills
- Delay Fills
- Vocal PA
- Presentations

Features:

- 550 Watt
- Full Range
- 60° dispersion
- Arrayable

Usage:

- Fly vertical
- Fly as downfill
- Pole mount
- Floor standing

The MP550 is an ultra versatile 550W, passive two way (full range) multipurpose speaker. Lightweight and versatile it is ideal as a stage monitor/ DJ monitor as well as for vocal PA, zone and delay reinforcement. For use on corporate events and multimedia presentations the MP550 speaker can

be flown horizontally or vertically and in multiple arrays for wide coverage. The MP550 is available with either left or right hand horn HF orientation and can be used with Opus SB series sub bass cabinets. Each speaker is supplied with its own specified 10m cable.



| | |
|------------------------------------|--|
| Configuration | 2-way passive |
| Devices | Bass/mid 1 x 15" HF: 1 x 1,4" |
| Frequency response (+/- 3dB) | 50Hz - 20kHz |
| Passive crossover | 24dB/Octave asymmetric |
| Output sensitivity (dB SPL 1W@1m) | Bass/mid 99dB HF: 112dB |
| Maximum SPL (@1m) | 132dB |
| Dispersion (horizontal x vertical) | 60° x 60° |
| RMS (Watt) | 550W |
| Dispersion mechanism: | LF: Reflex loaded HF: Constant directivity |
| Dimensions mm approx | Width front: 475mm Width back: 115mm Height: 765mm Depth: 490mm |
| Weight (approx) | 41kg |
| Construction | 18mm Baltic birch ply, hard carpet or custom finish |
| Fittings (optional) | 5 x Flying points 2x Flip handles |
| Accessories | Cover |



Opus Audio Technologies Ltd
Unit 39E, Fennel Business Park
Pennygillam Industrial Estate
Launceston, Cornwall, PL15 7ED

Tel: +44 (0) 1566 777332
Fax: +44 (0) 1566 777030
E-mail: info@opusaudio.com
Web: www.opusaudio.com

Move Beyond the Industry Standard