

# MP400N Speaker

## OPUS INTEGRATED SYSTEM™ COMPONENT SPECIFICATIONS

### Applications:

- Stage Monitors
- DJ Monitors
- Zone Fills
- Delay Fills
- Vocal PA
- Presentations

### Features:

- 400 Watt
- Full Range
- 60° dispersion
- Arrayable

### Usage:

- Fly vertical
- Fly as downfill
- Pole mount
- Floor standing

The MP400 is an ultra versatile 400W, passive two way (full range) multipurpose speaker. Lightweight and versatile it is ideal as a stage monitor/ DJ monitor as well as for vocal PA, zone and delay reinforcement. For use on corporate events and multimedia presentations the MP400 speaker can

be flown horizontally or vertically and in multiple arrays for wide coverage. The MP400 is available with either left or right hand horn HF orientation and can be used with Opus SB series sub bass cabinets. Each speaker is supplied with its own specified 10m cable.



Configuration	2-way passive
Devices	Bass/mid 1 x 12" HF: 1 x 1.4"
Frequency response (+/- 3dB)	60Hz - 20kHz
Passive crossover	24dB/Octave asymmetric
Output sensitivity (dB SPL 1W@1m)	Bass/mid 99dB HF: 112dB
Maximum SPL (@1m)	132dB
Dispersion (horizontal x vertical)	60° x 60°
RMS (Watt)	400W
Dispersion mechanism:	LF: Reflex loaded HF: Constant directivity
Dimensions mm approx	Width front: 425mm Width back: 120mm Height: 655mm Depth: 440mm
Weight (approx)	36kg
Construction	18mm Baltic birch ply, hard carpet or custom finish
Fittings (optional)	5 x Flying points 2x Flip handles
Accessories	Cover



**Opus Audio Technologies Ltd**  
Unit 39E, Fennel Business Park  
Pennygillam Industrial Estate  
Launceston, Cornwall. PL15 7ED

Tel: +44 (0) 1566 777332  
Fax: +44 (0) 1566 777030  
E.mail: [info@opusaudio.com](mailto:info@opusaudio.com)  
Web: [www.opusaudio.com](http://www.opusaudio.com)

Move Beyond the Industry Standard